



Gas Carrier SYN ANTARES

Type of Ship	Ethylene Carrier
Year	2014
Flag	Italian
Builder	Stocznia Gdansk Poland
Class Society	RINA
Class Notation	C* Liquefied gas carrier; unrestricted navigation
Additional Notation	*AUT-PORT; *AUT-UMS; *AVM-APS; CLEAN-SEA; INWATER SURVEY; MON-SHAFT
IMO Number	9512848

GENERAL INFO

Type of Ship	Ethylene Carrier
Year	2014
Flag	Italian
Builder	Stocznia Gdansk Poland
Class Society	RINA
Class Notation	
C* Liquefied gas carrier; unrestricted navigation	
Additional Notation	
*AUT-PORT; *AUT-UMS; *AVM-APS; CLEAN-SEA; INWATER SURVEY; MON-SHAFT	
IMO Number	9512848

MAIN DATA

LOA	122.87 mt
LBP	115.50 mt
Breadth	19 mt
Depth Mould	9.5 mt
K.T.M.	34.30 mt
Air Draught (normal ballast)	27.80
Summer draught	8.0 mt
Corresponding DWT	9230 - MT
Loaded Displacement	13226.60 - MT
Light Displacement	3996.40 - MT
TPC on Summer Draught	19.85 - MT
Int. GRT	7610
Int. NRT	2506
Suez GRT	8763
Suez NRT	7450

BUILT

Shipyard	Stocznia Gdansk Poland
Delivery Date	16/05/2014

CLASS

RINA/BV	RINA 85215
---------	------------

MAIN ENGINE

Type	Wartsila W9L32
Power	4500 - Kw
Fuel Grade	IFO 380

AUXILIARY NENGINE

Number	4
Type	VOLVO PENTA D34 AMS
Power	761 - Kw
Fuel Grade	Gasoil

SHAFT GEN.

Shaft Gen.	1104 - Kw
------------	-----------

BOW THRUSTER

Type	JASTRAM BU60
Power	450 - Kw

PROPELLER

Type	Pitch
------	-------

BUNKER

Capacity FO 100%	650 cbm
Capacity GO 100%	184 cbm

BALLAST

Capacity	3334.73 cbm
Number of Pumps	3
Pumping Capacity	600 - cbm/hr

LOADING

Capacity cbm/hr	max 1000 - cbm/hr
-----------------	-------------------

DISCHARGING

Capacity cbm/hr	1000 - cbm/hr
-----------------	---------------

FRESH WATER

Capacity of Tanks	195 - MT
Generated per Day	7 - MT

CROSSOVER

Distance Liquid 1 from bow	63.15
Distance Liquid 1 from stern	59.85
Distance Vapour 1 from bow	64.38
Distance Vapour 1 from stern	58.63
Distance Liquid 2 from bow	66.87
Distance Liquid 2 from stern	56.13
Distance Vapour 2 from bow	65.63
Distance Vapour 2 from stern	57.38

DISTANCE MANIFOLD

From Grating	1.25 mt
From Ship's Rail	2.70 mt
From Main Deck	6.05 mt
Abow W/L SDWT	7.55 mt
Abow W/L Ballast	9.05 mt

PARALLEL BODY LENGHT

At Summer Draught	71 mt
At Ballast Draught	54 mt

CARGO TANKS

Number	2
Type	Type C - x12 n15 steel en 10028-4
Max tank press IMO	5.7 - barg

Max tank press USCG	5.7 - barg
Max Vacuum	-0.75 - barg
Min. Temp.	-104Å°C - Å°C
Max Density/S.G.	0.97

TANKS CAPACITY

100%	8997 cbm
TK1	4383 cbm
TK2	4614 cbm

CARGO SEGREGATION

Number of Grades	2
List of Segregation	2

CARGO PUMPS

Type	Deepwell
Number	4
Capacity	250 - cbm/hr
M.L.C.	120
Max Density/S.G.	0.97

BOOSTER PUMP

Number	1
Capacity	250 - cbm/hr
M.L.C.	120
Max Density/S.G.	0.69

CARGO HEATER

Number	1
Heating Medium	Sea water exchange
Capacity	400 (sea water 25Å°C) - cbm/hr

CARGO COMPRESSORS

Number	2 + 2
Type	Sulzer + Howden

CRANE

Number (Hoisting Hoses)	1 - cn
SWL	4.0 - MT