



## Gas Carrier SYN ZUBE

Type of Ship	LPG Carrier
Year	2009
Flag	Italian
Builder	Cantieri Navali, Pesaro
Class Society	RINA/BV
Class Notation	C+ Liquefied gas carrier - unrestricted navigation
Additional Notation	+AUT-PORT; +AUT-UMS; +AVM-APS; CLEAN SEA; INWATERSURVEY; MON-SHAFT
IMO Number	9346940

**GENERAL INFO**

Type of Ship	LPG Carrier
Year	2009
Flag	Italian
Builder	Cantieri Navali, Pesaro
Class Society	RINA/BV
Class Notation	C+ Liquefied gas carrier - unrestricted navigation
Additional Notation	+AUT-PORT; +AUT-UMS; +AVM-APS; CLEAN SEA; INWATERSURVEY; MON-SHAFT
IMO Number	9346940

**MAIN DATA**

LOA	95.5 mt
LBP	86.35 mt
Breadth	15.5 mt
Depth Mould	8 mt
K.T.M.	31.00 mt
Air Draught (normal ballast)	26
Summer draught	6.5 mt
Corresponding DWT	4026 - MT
Loaded Displacement	2353 - MT
Light Displacement	6379 - MT
TPC on Summer Draught	12.3 - MT
Int. GRT	3827
Int. NRT	1148
Suez GRT	4176
Suez NRT	3106

**BUILT**

Shipyard	Cantieri Navali, Pesaro
Delivery Date	17/11/2009

**CLASS**

RINA/BV	100 A1-1/NAV. I.L CST
---------	-----------------------

**MAIN ENGINE**

Type	MAN B&W
Power	2380 - Kw
Fuel Grade	IFO 180

**AUXILIARY ENGINE**

Number	3
Type	VOLVO PENTA TAMD 165 A
Power	400 - Kw
Fuel Grade	Gasoil

**SHAFT GEN.**

Shaft Gen.	660 - Kw
------------	----------

**BOW THRUSTER**

Type	Brumvoll
Power	300 - Kw

**PROPELLER**

Type	Pitch
------	-------

**BUNKER**

Capacity FO 100%	313 cbm
Capacity GO 100%	114 cbm

**BALLAST**

Capacity	1586 cbm
Number of Pumps	3
Pumping Capacity	250 - cbm/hr

**LOADING**

Capacity cbm/hr	max 500 - cbm/hr
-----------------	------------------

**DISCHARGING**

Capacity cbm/hr	max 400 - cbm/hr
-----------------	------------------

**FRESH WATER**

Capacity of Tanks	80 - MT
Generated per Day	7 - MT

**CROSSOVER**

Distance Liquid 1 from bow	52.16
Distance Liquid 1 from stern	43.04
Distance Vapour 1 from bow	53.38
Distance Vapour 1 from stern	41.81
Distance Liquid 2 from bow	55.86
Distance Liquid 2 from stern	39.35
Distance Vapour 2 from bow	54.61
Distance Vapour 2 from stern	40.58

**DISTANCE MANIFOLD**

From Grating	1.1 mt
From Ship's Rail	1.3 mt
From Main Deck	4.8 mt
Abow W/L SDWT	5.2 mt
Abow W/L Ballast	6.9 mt

**PARALLEL BODY LENGHT**

At Summer Draught	54 mt
At Ballast Draught	45 mt

**CARGO TANKS**

Number	2
Type	Tyoe C Cylindric
Max tank press IMO	8 - barg
Max tank press USCG	5 - barg

Max Vacuum	-0.25 - barg
Min. Temp.	-48 - Å°C
Max Density/S.G.	0.97

#### TANKS CAPACITY

100%	4.007,1 cbm
TK1	1.955,2 cbm
TK2	2.051,9 cbm

#### CARGO SEGREGATION

Number of Grades	2
List of Segregation	1-2

#### CARGO PUMPS

Type	Deepwell Swanehoy
Number	2
Capacity	250 - cbm/hr
M.L.C.	120
Max Density/S.G.	0.97

#### BOOSTER PUMP

Number	1
Capacity	250 - cbm/hr
M.L.C.	120
Max Density/S.G.	0.68

#### CARGO HEATER

Number	1
Heating Medium	sea water
Capacity (sea water 15Å??Å?Å°C)	370 - cbm/hr

#### CARGO COMPRESSORS

Number	2
Type	Sulzer 2K 140-2F/S/i

#### CRANE

Number (Hoisting Hoses)	
Number (Hoisting Hoses)	
SWL	3 - MT